

RHINO-FR

Ram Resistant Folding Doors



Rhino Doors

THE STRENGTH TO PROTECT

Rhino-FR Folding Doors

Designed to resist vehicle ram attack

Comprised of any number of high strength panels that can part at any section along the width of the doors, providing greater operational flexibility. The panels fold away into compact areas at the sides of the opening.

- | | |
|-----------------------|---|
| Tested to: | PAS68 (amended) |
| Optional ratings: | UK Government CPNI security standard
Blast resistance
Ballistic resistance to FB4/G2
Ram Resistance |
| Configurations: | Sliding folding and bi-parting sliding folding |
| Maximum opening size: | 48m x 11m high |
| Door Panels: | Available 40 & 60mm thick with steel skins
Composite attack resistant core
Vertical steel box section joints sealed with dovetailed EDPM seals
Solid steel hinges with grease nipple lubricated and phosphor bronze bushes |
| Guides and rails: | Heavy duty top supported tracks at the head fitted with 'sealed for life' Nylatron bearings
Bottom track guide rail manufactured from heavy gauge mild or stainless steel |
| Operation: | Manual only |
| Drop bolts: | Manual or electrically operated |
| Optional extras: | Wicket door for personnel access
Louvres
Glazing
Bi-parting option tailored to crane rail protrusions |
| Optional Finishes: | 'Colorcoat' sheets from a range of standard colours
Galvanised steel
Finish painted in a choice of colours |



Rhino-FC Folding Door



Rhino-FC Bi-Parting Folding Door



Rhino-FC Bi-Folding Door



Contact Details

Rhino Systems Ltd

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0)1639 888 119

F: +44 (0)1639 898 119

enquiries@rhinodoors.com

www.rhinodoors.com

