

Product datasheet: PD05

RHINO-HF

Fire Rated Door Set



Rhino Doors

THE STRENGTH TO PROTECT

Rhino-HF fire rated doors are used for fire compartmentalisation purposes inside commercial and industrial buildings

RHINO-HF door sets are designed and manufactured to BS EN 9001 Quality Assurance Standards. They have been fully fire tested at Warrington Fire and are CERTIFIRE third party product certified to comply with BS EN 1634-1.

Fire rating:	Up to E240 (integrity only) to EN1634-1 CERTIFIRE certificate no CF5108
Configurations:	Single swing Single, double and unequal leaf Fixed/Removable over panels Side panels Latched and un-latched
Construction details:	
Leaf:	45mm thick with 1.2mm zintec coated steel skins with a rebated leading edge and a bonded structural honeycomb core 7 No heavy-duty dog bolts on the hinge edge
Frame:	90mm to 150mm deep butt jointed, single rebate profile brake-pressed from 1.5mm thick zintec coated steel
Threshold:	15mm aluminium raised threshold with integral tubular silicone rubber seal)
Seals:	Tubular silicone rubber located in the frame rebate on three sides
Ironmongery:	3 No stainless-steel butt hinges per leaf Overhead closers
Vision panels	Choice of sizes
Surface finish:	PPC to any RAL colour as standard



Contact Details

Rhino Systems Ltd

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0)1639 888 119

F: +44 (0)1639 898 119

enquiries@rhinodoors.com

www.rhinodoors.com



'A portfolio company of Cyrus Investment Management LLP'