

RHINO-WT^{2/3/4}

Security Rated Floodproof Doors



Rhino Doors

THE STRENGTH TO PROTECT

Rhino-WT flood defence doors are available with physical attack resistance to levels SR2, SR3 & SR4

Rhino-WT flood proof door sets are designed and manufactured to BS EN 9001 Quality Assurance Standards.

Performance ratings: Watertight to 870mm to PAS 1188-1: 2014
Physical attack resistance certified by the Loss Prevention Certification Board (LPCB) to LPS 1175 (Issue 7) levels SR2, SR3 & SR4.

Configuration: Single swing
Single, double and unequal leaf
Outward opening only
Double leaf doors supplied with a removable centre mullion
Fixed over panels
(Integral escape hatches, independently locked for access and egress in flood situations)

Construction details:

Leaf: 60mm thick with 1.5mm zintec coated steel skins with a rebated leading edge and a steel stiffened core
Astragal 10mm steel

Frame: 120mm deep single rebate constructed from 80x40mm sections

Seals: Integral EDPM flood seal and anti-pry strip to leading edge

Ironmongery: 3 No bearing mounted lift-off hinges
External stainless-steel lever handle with key

Overhead closers and friction stays

Vision panel Above 1000mm FFL

Louvre Bladed cartridges above 1000mm FFL

Surface finish: (PPC to any RAL colour)
(Full gloss)



Contact Details

Rhino Systems Ltd

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0)1639 888 119

F: +44 (0)1639 898 119

enquiries@rhinodoors.com

www.rhinodoors.com



'A portfolio company of Cyrus Investment Management LLP'