

Product datasheet: PD02

# RHINO-SC

CPNI Security Rated Sliding Doors



Rhino Doors

THE STRENGTH TO PROTECT

## Rhino-SC Sliding Doors

Designed to resist deliberate forced entry, blast, vehicle ram and ballistic attacks  
Comprised of multiple panels forming one or more rigid door leaves that can slide directly into a storage area to create minimum intrusion into the internal space.

Tested to:	UK Government CPNI security standard
Optional ratings:	Blast resistance Ballistic resistance to FB4/G2 Ram Resistance to BSi PAS68 (amended)
Configurations:	Sliding folding and bi-parting sliding folding
Maximum opening sizes:	26000 x 8000mm 4000 x 8000mm high in bi-parting configurations (w x h)
Door Panels:	Available 40 & 60mm thick with steel skins Composite attack resistant core
Guides and rails:	Vertical steel box section Heavy duty top supported tracks at the head fitted with 'sealed for life' Nylatron bearings Bottom track guide rail manufactured from heavy gauge mild or stainless steel
Operation:	Available with manual and fully automatic operation, ground supported or top hung
Drop bolts:	Manual or electrically operated
Optional extras:	Wicket door for personnel access Louvres Glazing Bi-parting option tailored to crane rail protrusions
Finishes:	'Colorcoat' sheets from a range of standard colours Galvanised steel Finish painted in a choice of colours



Rhino-SC Sliding door



Rhino-SC Sliding door



### Contact Details

#### Rhino Systems Ltd

Maritime Road  
Llewellyns Quay  
Port Talbot  
SA13 1RF

T: +44 (0)1639 888 119

[enquiries@rhinodoors.com](mailto:enquiries@rhinodoors.com)  
[www.rhinodoors.com](http://www.rhinodoors.com)

