

# RHINO-HA

Sound Reducing Doors



Rhino Doors

THE STRENGTH TO PROTECT

Rhino-HA acoustic doors are used to suppress unwanted sound inside and outside commercial and industrial buildings

Rhino-HA door sets are designed and manufactured under a Quality Management System certified to meet the requirements of BS EN ISO 9001.

Performance rating:  $R_w$  40dB attenuation ISO 10140-2: 2010

Configuration: Single swing  
Single, double and unequal leaves  
Fixed/Removable over panels  
Side panels  
Latched

Construction details:

Leaf: 45mm thick with 1.2mm zintec coated steel skins with a rebated leading edge and a bonded plasterboard and mineral wool core

Frame: 90mm (150mm) deep butt jointed, single rebate profile brake-pressed from 1.5mm thick zintec coated steel

Threshold: 15mm aluminium raised threshold with integral tubular silicone rubber seal

Seals: Tubular silicone rubber located in the frame rebate on three sides

Ironmongery: 3 No stainless steel butt hinges per leaf  
Sash lock with stainless steel lever handle

Overhead closer type ...

Vision panel Choice of sizes

Surface finish: PPC to any RAL colour



Contact Details

**Rhino Systems Ltd**

Maritime Road  
Llewellyns Quay  
Port Talbot  
SA13 1RF

T: +44 (0)1639 888 119

[enquiries@rhinodoors.com](mailto:enquiries@rhinodoors.com)  
[www.rhinodoors.com](http://www.rhinodoors.com)