

RHINO-HF+^{2/3/4}

Premium Multi-Performance Rated Door Sets



THE STRENGTH TO PROTECT

Rhino-HF+ premium multi-performance fire rated doors are used for internal and external applications in commercial and industrial buildings.

Performance ratings: Up to E240 (integrity only) to EN1634-1: CERTIFIRE certificate no CF5786
Physical attack resistance certified by the Loss Prevention Certification Board (LPCB) to LPS 1175 (Issue 7) levels SR2, SR3 & SR4.
Blast rated up to 10kPa
Static pressure rated to 10kPa

Configurations: Single swing
Single, double and unequal leaf
Fixed/Removable over panels
Side panels

Leaf: 66mm thick with 1.5mm zintec coated steel skins with a rebated leading edge and a steel stiffened core
9 No dog bolts on the hinge edge
Astragal 10mm steel

Frame: 110mm deep single rebate profile brake-pressed from 2mm thick zintec coated steel

Threshold: 15mm low profile aluminium or steel raised threshold with integral tubular silicone rubber seal

Seals: Tubular silicone rubber located in the frame rebate on three sides

Ironmongery: 3 No stainless-steel butt hinges per leaf
Overhead closers

Vision panels Choice of sizes

Surface finish: PPC to any RAL colour as standard



Contact details

Rhino Systems Limited

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0) 1639 888 119

info@rhinodoors.com
www.rhinodoors.com



Raising Standards
Advancing Safety

