

# RHINO-WT<sup>2/3/4</sup>

Security Rated Floodproof Doors



Rhino Doors

THE STRENGTH TO PROTECT

Rhino-WT flood defence doors are available with physical attack resistance to levels SR2, SR3 & SR4

Rhino-WT flood proof door sets are designed and manufactured under a Quality Management System certified to meet the requirements of BS EN ISO 9001.

Performance ratings: Watertight to 870mm to PAS 1188-1: 2014

Physical attack resistance certified by the Loss Prevention Certification Board (LPCB) to LPS 1175 (Issue 7) levels SR2, SR3 & SR4.

**Configuration:** Single swing  
Single, double and unequal leaf  
Outward opening only  
Double leaf doors supplied with a removable centre mullion  
Fixed over panels (Integral escape hatches, independently locked for access and egress in flood situations)

**Construction details:**

**Leaf:** 60mm thick with 1.5mm zintec coated steel skins with a rebated leading edge and a steel stiffened core  
Astragal 10mm steel

**Frame:** 120mm deep single rebate constructed from 80x40mm sections

**Seals:** Integral EDPM flood seal and anti-pry strip to leading edge

**Ironmongery:** 3 No bearing mounted lift-off hinges  
External stainless-steel lever handle with key

Overhead closers and friction stays

**Vision panel** Above 1000mm FFL

**Louvre** Bladed cartridges above 1000mm FFL

**Surface finish:** (PPC to any RAL colour) (Full gloss)  
(Semi-gloss) (Marine grade)



Contact Details

**Rhino Systems Ltd**

Maritime Road  
Llewellyns Quay  
Port Talbot  
SA13 1RF

T: +44 (0)1639 888 119

[enquiries@rhinodoors.com](mailto:enquiries@rhinodoors.com)  
[www.rhinodoors.com](http://www.rhinodoors.com)

