

RHINO-FD120HL



Premium Fire Rated Door Sets

THE STRENGTH TO PROTECT

Rhino-FD120HL premium fire rated latched doors are used mainly for internal and external applications in commercial and industrial buildings.

- Performance ratings:** Up to E120 (integrity only) to EN1634-1.
- Certificate No.** IFCC 1692
<https://www.ifccertification.com/>
- Configurations:** Single swing
Double and unequal leaf, normally held open option. Clear openings up to 2120 x 2100mm
- Leaf:** 55mm thick with 1.5mm stainless steel skins with a stainless steel stiffened core
Non-rebated leading edge to allow independent leaf operation
- Edge** Flush
- Frame:** 120mm deep single rebate profile from 2.0mm thick stainless steel
- Threshold:** None
- Seals:** Intumescent fire and smoke strip on three sides of leaves
- Ironmongery:** 3 No. stainless steel butt hinges per leaf
Concealed panic bolts with lever handle / push pad operation
Overhead closers
- Vision panels** Choice of sizes
- Surface finish:** Stainless Steel (any finish) or carbon steel with PPC to any RAL colour as standard



INWARD OR OUTWARD OPENING



Contact details

Rhino Systems Limited

Maritime Road
Llewellyns Quay
Port Talbot
SA13 1RF

T: +44 (0) 1639 888 119

info@rhinodoors.com
www.rhinodoors.com



Raising Standards
Advancing Safety

