

# RHINO-FD90SLP



Premium Fire Rated Door Sets

THE STRENGTH TO PROTECT

**Rhino-FD90SLP** premium fire rated sliding doors are used mainly for cross passage escape routes (road & rail tunnels) and can also be specified for other applications.

**Performance ratings:** Up to E90 (integrity only) from both sides to NFPA 252. Assessed performance of 60 minutes integrity to BS 476: Part 22: 1987, Clause 8.

Pressure in excess of +/-7.5kPa (both sides) and fatigue load >2.5kPa. 10<sup>6</sup> cycles per year, +25 year design life.

**Certificate No.** IFCC 1838  
<https://www.ifccertification.com/>

**Configurations:** Sliding single leaf – self closing. Can be 'normally held open' to self close on fire / smoke alarm. Top hung with bottom guide rollers (no threshold). Clear opening up to 1120 mm wide x 2100 mm high.

**Leaf:** 106 mm thick mild steel with stiffened core, 3 mm thick skins to both faces.

**Edge:** Flush, to engage in frame slam post.

**Frame:** Rebated profile in 3 mm thick mild steel.

**Threshold:** None

**Seals:** Intumescent fire seals fitted to frame profile.

**Ironmongery:** Heavy duty 'D' pull handles to both faces.

**Vision panels:** Not applicable.



## Contact details

### Rhino Systems Limited

Maritime Road  
Llewellyns Quay  
Port Talbot  
SA13 1RF

T: +44 (0) 1639 888 119

info@rhinodoors.com  
[www.rhinodoors.com](http://www.rhinodoors.com)



Raising Standards  
Advancing Safety

