

RHINO-HCFD60

NPSA SECURITY RATED PERSONNEL DOORS

PRODUCT DATASHEET: PD18



Rhino-HCFD60
Double Leaf



Rhino-HCFD60
Single Leaf



Rhino-HCFD60 Government security & fire rated hinged doors

Designed to resist deliberate forced entry, blast, vehicle ram and ballistic attacks, together with a fire rating of 60 minutes integrity, 30 minutes insulation.

NPSA rated product:
Approved for UK
Government use, for
details contact NPSA

Tested to

UK Government NPSA (was CPNI) MFES security standard & fire rated EN1634-1, E60, I30

Fire Certificate No

IFCC 1747

<https://www.ifccertification.com/>

Optional ratings

Blast resistance

Ballistic resistance to FB4/G2

Acoustic rating up to R_w43dB

Configurations

Single and double leaf, single swing with side and over panels

Maximum opening size

2800x2400mm (w x h)

Leaf

90mm thick with a steel clad box section framework

Frame

Steel box section

Mitred and butt welded and filled with insulation material, and a welded steel box section stop

Ironmongery

Solid steel hinges with grease nipple lubricated and phosphor bronze bushes

High security locks

Optional extras

Stand-alone stainless steel dog bolts

Finishes

'Colorcoat ®' sheets from a range of standard colours

Galvanised steel

Powder coated in a choice of RAL colours