

RHINO-WT 2/3/4

SECURITY RATED FLOODPROOF DOORS

PRODUCT DATASHEET: **PD08**



Rhino-WT+
Double Leaf



Rhino-WT+
Single Leaf



Rhino-WT flood defence doors are available with physical attack resistance to levels SR2, SR3 or SR4

The superscript number WT², WT³ or WT⁴ refers to the security rating SR2, SR3 or SR4 respectively

Performance ratings

Watertight to 870mm to PAS 1188-1: 2014

Physical attack resistance certified by the Loss Prevention

Certification Board (LPCB) to LPS 1175 (Issue 7) levels SR2, SR3 & SR4.

Configurations

Single swing

Single, double and unequal leaf

Outward opening only

Double leaf doors supplied with a removable centre mullion

Fixed over panels (Integral escape hatches, independently locked for access and egress in flood situations)

Leaf

60mm thick with 1.5mm zintec coated steel skins with a rebated leading edge and a steel stiffened core

Astragal 10mm steel

Frame

120mm deep single rebate constructed from 80x40mm sections

Seals

Integral EDPM flood seal and anti-pry strip to leading edge

Ironmongery

3 No bearing mounted lift-off hinges

External stainless-steel lever handle with key

Overhead closers and friction stays

Vision panel

Above 1000mm FFL

Louvre

Bladed cartridges above 1000mm FFL

Surface finish

(PPC to any RAL colour) (Full gloss)
(Semi-gloss) (Marine grade)