

RHINO-SL

NPSA SECURITY RATED SLIDING DOORS

PRODUCT DATASHEET: **PD13**



Rhino-SL
Sliding Door



Rhino-SL Sliding Doors

Designed to resist deliberate forced entry, blast, vehicle ram and ballistic attacks.

Comprised of multiple panels forming one or more rigid door leaves that can slide directly into a storage area to create minimum intrusion into the internal space.

LPCB rated high security product

Tested to

LPS1175: Issue 8

Security Rating **G5**

Optional ratings

Blast resistance

Ballistic resistance to FB4/G2

Ram Resistance to BSi

PAS68 (amended)

Configurations

Sliding and bi-parting sliding

Maximum opening size

27600 x 7000mm

Door Panels

100mm thick with steel skins

Composite attack resistant core

Vertical steel box section

Guides and rails

Heavy duty top supported tracks at the head fitted with 'sealed for life' Nylatron bearings

Bottom track guide rail manufactured from heavy gauge mild or stainless steel

Operation

Available with manual and semi automatic operation, ground supported or top hung

Drop bolts

Manual or electrically operated

Optional extras

Wicket door for personnel access

Louvres

Glazing

Bi-parting option tailored to crane rail protrusions

Finishes

'Colorcoat' sheets from a range of standard colours

Galvanised steel

Finish painted in a choice of colours